

PRODUCT DATA SHEET

STYLE NO.: **4811E**



This general service packing has a strand locking braid made from synthetic fibers that have been thoroughly impregnated with petroleum based lubricants and coated with graphite flake. Our 4811E offers a dense but flexible packing.

We also offer this as a traditional square braid packing for older and worn shafts and sleeves as 4811D

WICK (BODY) MATERIAL:	Synthetic carded yarns
SURFACE LUBRICANT:	Graphite flake
INTERIOR LUBRICANT:	Petroleum based lubricant
CONSTRUCTION (BRAID):	4811D Square braid 4811E Strand Locking
CONSTRUCTION (ADDITIONAL):	None
SPECIFICATIONS MET:	None

APPLICATIONS: Centrifugal and reciprocating pumps, valves, mixers, agitators and expansion joints. Water, steam, gasses, air, brine, petroleum products – oils and fuels, slurries waste, sludges. A good general service packing.

Temperature (F°)	-50°F	===== +350°F
pH Range (0 – 14)	4=====	=====10
Speed in F.P.M.	=====1600	

FEET PER POUND

INCHES	1/8	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4
POUNDS	161.0	71.4	40.2	26.8	17.9	13.4	10.3	6.5	4.5