



Available in all sizes and ratings!

Teflon® Flange Shield

SAFETY IS NEVER "OPTIONAL"

Workplace safety is critical. MPRCseals.com offers Teflon Flange Shields to ensure the safety and protection of your operations and keep workplace safety in the forefront. Leaks can occur on piping systems conveying chemicals, high temperature fluids, and steam- potentially harming workers, the environment, and damaging equipment.

These shields are designed to prevent an accident by temporarily containing hazardous leaks and sprays, and offer the following features and benefits:

- Transparent Clear Teflon® center strip allows for complete visual inspection.
- Sides constructed of Premium Teflon® coated glass cloth.
- Teflon® coated fiberglass or Nomex® thread and draw cord.
- Fire and tear resistant.
- Optional 1/2" diameter Teflon® drain nipple.
- Max operating temperature 400°F.

CHEMICAL	MAXIMUM TEMPERATURE °F
Ammonia	200
Ethylene Dichloride	75
Hydrochloric Acid (to 35% conc.)	400
Hydrofluoric Acid (to 85% conc.)	Not Recommended
Nitric Acid (to 30% conc.)	300
Oleum	75
Sodium Hydroxide (to 50% conc.)	300
Sulfuric Acid (to 30% conc.)	300

Call Master Packing & Rubber Company today for a quote at 800-397-3429, or visit us at MPRCseals.com

MASTER PACKING & RUBBER COMPANY

An ISO 9001:2015 Certified Company



6430 4th Street SW • Cedar Rapids, Iowa 52404

Phone: (319) 364-8282 • Toll Free: (800) 397-3429 • Fax: (319) 364-8266

On the Web @ www.MPRCseals.com

